








Technical specifications / Especificaciones

	Engine / Motor	
	Gas / Gasolina	Honda GX 270 9hp
	Transmission / Transmisión	
	Type / Tipo	Hydrostatic / Hidrostática
	Hydraulic pump / Bomba hidráulica	2x variable displ / 2x port.variable
	Hydraulic system / Sistema hidráulico	
	Hydraulic pump / Bomba hidráulica	Gear pump / Equipo
	Flow Std / Flujo Std	1x13.5 l/min (1x3.6 gpm)
	Hi-flow / Flujo Hi-Flow	1x22 l/min (1x5.8 gpm)
	Max pressure / Presión Máxima	150 bar (2180 psi)
	Tracks / Sistema de rodamiento	
	Stand. Track Width / Ancho de la Oruga Stand.	180 mm (7.1 in)
	Rocking Rollers / Rodillos Oscilantes	Yes / Si
	Performance and dimensions / Rendimiento y dimensiones	
	Max. Travel Speed / Velocidad Max.	0-4.5 Km/h (0-2.8 mph)
	Operative weight / Capacidad operativa	650 Kg (1432 lb)
	Dry Weight / Peso del Equipo	430 kg (992lb) ² < - > 500 kg (1102lb) ³ < - > 630kg (1389lb) ³
	Standard tip skip / Cajon Volqueta	1150 x 800 x 350 mm (45.3x31.5x13.8 in) ³
	Standard tip skip / Cajon Volqueta	1150 x 680 x 350 mm (45.3x26.8x13.8 in) ³
	Agricultural Skip / Caja Agrícola	1100 (1350 max) x800 (1300 max) mm x 250 mm ⁵
	Agricultural Skip / Caja Agrícola	43.3 (53.1 max) in x 32.5 (51.2 max) in x 9.8 in ⁵

1) Optional / opcional 2) Standard tip type / Estándar 3) Self loading type / Autocaricante
4) Hi-tip type / Versión de descarga de alta 5) Only for standard tip type / Sólo para la Std

